

ATTENUATOR ARROW BOARD

MODELS FOR THE SCORPION AND THE VORTEC*

K&K manufacturers 15 and 25 lamp Arrow Boards and mount specific for Attenuators. The 12V linear actuator with built-in limit switches and 6" stroke and features an auto raise/lower function. A built-in controller on the display face allows operation without a remote. Wireless and wired remotes are available for convenient operation.



FEATURES

- ▶ Arrow Board Meets MUTCD standards
- ▶ Photocell for Auto Dimming
- ▶ Super Bright LED Technology
- ▶ Easy to Operate & Maintain Arrow Board
- Durable Powder Coat Finish
- ▶ 360° LED Visors
- ▶ 8 Function Control Arrow Board
- ▶ 30-40 Flash Rate
- Mounting Options
- ▶ Durable Finish Resists the Elements
- ▶ Lightweight Construction
- Meets the 7 ft. min. mounting height with optional over-the-cab mounting hardware



MODEL SCORPION / VORTEC VEHICLE MOUNT ARROW BOARD SERIES





OPTIONAL REMOTES AVAILABLE

The K&K Arrow Boards have a standard built-in controller on the display face. Optional wireless or wired remotes are available for easy operation and mode selection.



CONTROLLER

Battery Status Indicator

Light: Indicates if solar is charging and its progress. Multi-color LED indicates the battery condition (low, fair, or good).

Error LED: Indicates low voltage disconnect or over voltage condition **Mode Selector:** Capable of 8 modes in 15 lamp configuration

SIGN DISPLAY

Construction: Height: 48"

Length: 96" Width: 33/8"

Material: • 1/8" Aluminum frame 36"x72" w/ (2) 35¾" cross members

• .063 Aluminum composite front panel 36"x72" • .063 Aluminum composite back panel 36"x72"

Salt Spray Fog: 1,000 hours

UV Resistance: 500 hours

LED bulbs: (15) yellow/amber Par 46 LED's with 360° high impact visor. Push on type connectors to prevent separation due to vibration during travel and operation.

OPTIONS

- ▶ Three small amber indicator lights added to the back of display
- ▶ Hitch mount
- Low profile mount with 12V linear actuator
- Over cab mount. Also requires (low profile mount)
- ► Tailgate mount
- Upgrade to 25′, 40′, or 60′ power cable
- ▶ Two-tube frame for rail mount
- Upgrade to TruWireless complete wireless operation